

# FUENTE SWITCHING 360W



De fácil instalación gracias a su tamaño compacto.  
Alta eficiencia de transferencia.  
100% Loaded. Protección contra corto-circuito.

VOLTAJE DE SALIDA 12V / 24V    CARGA 360 W    EFICIENCIA 83%

# FUENTE SWITCHING 360W

## ESPECIFICACIONES TÉCNICAS

CÓDIGO	8PS120360DCU	8PS240360DCU
<b>DC Voltage</b>	12V	24V
<b>Rated current</b>	30A	15A
<b>Rated power</b>	360W	360W
<b>Ripple &amp; noise (max)</b>	<120mVp-p	<120mVp-p
<b>Setup, rise time</b>	1500ms/230VAC	1500ms/230VAC
<b>Line regulation</b>	1%	1%
<b>Load regulation</b>	1%	1%
<b>INPUT</b>		
<b>Voltage</b>	170-250V	170-250V
<b>Frecuency</b>	50/60Hz	50/60Hz
<b>Efficiency</b>	83%	83%
<b>Power factor</b>	0.6	0.6
<b>Current</b>	230V:3.2A max.	230V:3.2A max.
<b>Inrush current</b>	40A	40A
<b>PROTECTION</b>		
<b>Open circuit</b>	Yes, cut-off mode. Output shuts down if overloaded.	
<b>Short circuit</b>	Yes, output shut down, recovers automatically after fault condition is removed.	
<b>ENVIRONMENT AND OTHERS</b>		
<b>Working temperature</b>	-30-60°C	-30-60°C
<b>Working humidity</b>	20-95%RH	20-95%RH
<b>Storage temp.</b>	-40-80°C	-40-80°C
<b>Storage humidity</b>	10-95%RH	10-95%RH
<b>Life spam</b>	50K hours @ 20 °C working temperature	50K hours @ 20 °C working temperature
<b>STANDARD REQUEST</b>		
<b>Safety</b>	EN61347-2-13	EN61347-2-13
<b>Withstand voltage</b>	I/P-0/P:1500VAC/1min/<5mA	I/P-0/P:1500VAC/1min/<5mA
<b>Isolation resistance</b>	I/P-0/P:>100M Ohms / 500VDC / 25°C / 70%RH	I/P-0/P:>100M Ohms / 500VDC / 25°C / 70%RH
<b>DIMENSIONES</b>	215x114x49 mm	